



GB

Page 1 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 13.02.2015 / 0001
Replaces revision of / Version: 13.02.2015 / 0001
Valid from: 13.02.2015
PDF print date: 25.03.2015
Smite Organic Killa Spray

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Smite Organic Spray

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Insecticide

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

PestTrappa, Whittington Way, Chesterfield, S41 9AG

Qualified person's e-mail address: info@smite-a-mite.com Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone

Emergency information services / official advisory body:

+44 01246 264635

Telephone number of the company in case of emergencies:

GB

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

F+, Extremely flammable

Xi, Irritant, R36

R67

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 13.02.2015 / 0001
 Replaces revision of / Version: 13.02.2015 / 0001
 Valid from: 13.02.2015
 PDF print date: 25.03.2015
 Smite Organic Killa Spray



Danger

H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear eye protection.
 P312-Call a POISON CENTER/doctor if you feel unwell.
 P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
 P501-Dispose of contents/container safely.

Without adequate ventilation, formation of explosive mixtures may be possible.
 Propan-2-ol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

Propan-2-ol	
Registration number (REACH)	01-2119457558-25-XXXX
Index	603-117-00-0
EINECS, ELINCS, NLP	200-661-7
CAS	CAS 67-63-0
content %	35
Classification according to Directive 67/548/EEC	Highly flammable, F, R11 Irritant, Xi, R36 R67
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 13.02.2015 / 0001
Replaces revision of / Version: 13.02.2015 / 0001
Valid from: 13.02.2015
PDF print date: 25.03.2015
Smite Organic Killa Spray

4.1 Description of first aid measures

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.
The following may occur:

Coughing
eyes, reddened
Watering eyes
drowsiness
drowsiness
Narcotic effect.
Unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed

Elementary aid
Decontamination
Symptomatic treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2
Foam
Dry extinguisher
Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Toxic gases
Danger of bursting (explosion) when heated
Explosive vapour/air mixture

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



GB

Page 4 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 13.02.2015 / 0001
 Replaces revision of / Version: 13.02.2015 / 0001
 Valid from: 13.02.2015
 PDF print date: 25.03.2015
 Smite Organic Killa Spray

Remove possible causes of ignition - do not smoke.
 Ensure sufficient supply of air.
 Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.
 Prevent surface and ground-water infiltration, as well as ground penetration.
 If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid inhalation of the vapours.
 Keep away from sources of ignition - Do not smoke.
 Take measures against electrostatic charging, if appropriate.
 Do not use on hot surfaces.
 Avoid contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Do not store with flammable or self-igniting materials.
 Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").
 Observe special regulations for aerosols!
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well-ventilated place.
 Store cool

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Propan-2-ol		Content %:35
WEL-TWA:	400 ppm (999 mg/m3)	WEL-STEL:	500 ppm (1250 mg/m3) ---
BMGV:	---	Other information:	---
Chemical Name	Butane		Content %:
WEL-TWA:	600 ppm (1450 mg/m3)	WEL-STEL:	750 ppm (1810 mg/m3) ---
BMGV:	---	Other information:	---
Chemical Name	Propane		Content %:
WEL-TWA:	1000 ppm (ACGIH)	WEL-STEL:	---

GB

Page 5 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 13.02.2015 / 0001
 Replaces revision of / Version: 13.02.2015 / 0001
 Valid from: 13.02.2015
 PDF print date: 25.03.2015
 Smite Organic Killa Spray

BMGV: ---	Other information: ---	
Chemical Name	Uncalcined diatomite	Content %:
WEL-TWA: 1,2 mg/m ³ (natural, resp. dust)	WEL-STEL: ---	---
BMGV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Propan-2-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term	DNEL	888	mg/kg	(1 d)
Workers / employees	Human - inhalation	Long term	DNEL	500	mg/m ³	
Consumer	Human - dermal	Long term	DNEL	319	mg/kg	(1 d)
Consumer	Human - inhalation	Long term	DNEL	89	mg/m ³	
Consumer	Human - oral	Long term	DNEL	26	mg/kg	(1 d)
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg	
	Environment - sediment, marine		PNEC	552	mg/kg	
	Environment - soil		PNEC	28	mg/kg	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Normally not necessary.
 In case of direct contact with the ingredients:
 Safety gloves made of butyl (EN 374)
 Protective Neoprene® / polychloroprene gloves (EN 374).
 Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:
 0,5
 Permeation time (penetration time) in minutes:
 480
 The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:

Page 6 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 13.02.2015 / 0001
 Replaces revision of / Version: 13.02.2015 / 0001
 Valid from: 13.02.2015
 PDF print date: 25.03.2015
 Smite Organic Killa Spray

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol, Substance: Liquid
Colour:	White
Odour:	Lemon
Odour threshold:	Not determined
pH-value:	~7
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	n.a.
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	n.a.
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	When using: development of explosive vapour/air mixture possible.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	~35 %

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 13.02.2015 / 0001
 Replaces revision of / Version: 13.02.2015 / 0001
 Valid from: 13.02.2015
 PDF print date: 25.03.2015
 Smite Organic Killa Spray

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

See also section 7.

Avoid contact with strong acids.

Avoid contact with strong alkalis.

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

InsectoSec® Insektenspray						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Propan-2-ol						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	30	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Eye Irrit. 2

Page 9 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 13.02.2015 / 0001
 Replaces revision of / Version: 13.02.2015 / 0001
 Valid from: 13.02.2015
 PDF print date: 25.03.2015
 Smite Organic Killa Spray

Propan-2-ol							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	9640	mg/l	Pimephales promelas		
Toxicity to daphnia:	EC50	48h	13299	mg/l	Daphnia magna		References
Toxicity to algae:	EC50	72h	>1000	mg/l	Desmodesmus subspicatus		
Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	
Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
Mobility in soil:	Koc		1,1				expert judgement
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Toxicity to bacteria:	EC10	18h	5175	mg/l	Pseudomonas putida	DIN 38412 T.8	
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	ThOD		2,4	g/g			
Water solubility:							Soluble

Butane							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Uncalcined diatomite							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 13.02.2015 / 0001

Replaces revision of / Version: 13.02.2015 / 0001

Valid from: 13.02.2015

PDF print date: 25.03.2015

Smite Organic Killa Spray

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

07 04 04 other organic solvents, washing liquids and mother liquors

16 05 04 gases in pressure containers (including halons) containing dangerous substances

Recommendation:

Pay attention to local and national official regulations

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

UN number: 1950

Transport by road/by rail (ADR/RID)

UN proper shipping name:

UN 1950 AEROSOLS

Transport hazard class(es):

2.1

Packing group:

-

Classification code:

5F

LQ (ADR 2015):

1 L

LQ (ADR 2009):

2

Environmental hazards:

Not applicable

Tunnel restriction code:

D



Transport by sea (IMDG-code)

UN proper shipping name:

AEROSOLS

Transport hazard class(es):

2.1

Packing group:

-

EmS:

F-D, S-U

Marine Pollutant:

n.a

Environmental hazards:

Not applicable



Transport by air (IATA)

UN proper shipping name:

Aerosols, flammable

Transport hazard class(es):

2.1

Packing group:

-

Environmental hazards:

Not applicable



Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Freight as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Page 11 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 13.02.2015 / 0001
 Replaces revision of / Version: 13.02.2015 / 0001
 Valid from: 13.02.2015
 PDF print date: 25.03.2015
 Smite Organic Killa Spray

Additional data acc. to Art. 69 (2), Regulation (EU) No 528/2012
 (Biocide products):

The identity of every active substance and its concentration in metric units:

Propan-2-ol
35 g/100 g

The uses:
Insecticide

License No. of the biocide (Regulation (EU) No 528/2012 / Directive 98/8/EC):
n.d.a.

Observe restrictions:
 Comply with trade association/occupational health regulations.
 Observe youth employment law (German regulation).

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections: n.a.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

11 Highly flammable.
 36 Irritating to eyes.
 67 Vapours may cause drowsiness and dizziness.
 H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Eye Irrit. — Eye irritation
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Aerosol — Aerosols
 Flam. Liq. — Flammable liquid

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
BMGV Biological monitoring guidance value (EH40, UK)
BOD Biochemical oxygen demand
BSEF Bromine Science and Environmental Forum
bw body weight
CAS Chemical Abstracts Service
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC Collaborative International Pesticides Analytical Council
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
COD Chemical oxygen demand
CTFA Cosmetic, Toiletry, and Fragrance Association
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
DT50 Dwell Time - 50% reduction of start concentration
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ERC Environmental Release Categories
ES Exposure scenario
etc. et cetera
EU European Union
EWC European Waste Catalogue
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
HET-CAM Hen's Egg Test - Chorionallantoic Membrane
HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container
IBC (Code) International Bulk Chemical (Code)
IC Inhibitory concentration
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
LC lethal concentration
LC50 lethal concentration 50 percent kill
LCLo lowest published lethal concentration
LD Lethal Dose of a chemical
LD50 Lethal Dose, 50% kill
LDLo Lethal Dose Low
LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities

Page 13 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 13.02.2015 / 0001
Replaces revision of / Version: 13.02.2015 / 0001
Valid from: 13.02.2015
PDF print date: 25.03.2015
Smite Organic Killa Spray

MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

PestTrappa, Whittington Way, Chesterfield, S41 9AG, Tel.: +44 01246 264635

© by PestTrappa. The copying or changing of this document is forbidden except with consent of PestTrappa™.